



Ø4.37 mm  
[.172 in]  
to suit an M4  
or #8 bolt (2 places)

56.00 mm  
[2.205 in]

30.58 mm  
[1.204 in]

50.39 mm  
[1.984 in]

(88.23 mm)  
[3.474 in]

30.99 mm  
[1.220 in]

33.28 mm  
[1.310 in]

**DETAIL A**

molded in Deutsch IPD receptacle,  
based on DT04-08PA, mates  
with DT06-08SA

48.71 mm  
[1.918 in]

33.28 mm  
[1.310 in]

70.00 mm  
[2.756 in]

10.80 mm  
[.425 in]



**label detail**

**TOLERANCES**

fabrication		machining	
X.XXX	+/- 0.015	X.XXX	+/- 0.001
X.XX	+/- 0.031	X.XX	+/- 0.005
X.X	+/- 0.031	X.X	+/- 0.015
fractional	+/- 0.031	fractional	+/- 0.031

MATERIAL  
injection molded  
glass filled PA66  
ultrasonically  
welded

DRAWN	DATE
TF	8/27/2015
CHECKED	DATE
DL	
APPROVED	DATE
DL	

TITLE		Dual Output CAN Controller, J1939	
DWG REV	DWG NO	PART NO	SHEET
D1	AX020200-MD	AX020200	1 of 1

PROPRIETARY  
THE INFORMATION CONTAINED IN THIS DRAWING IS CONFIDENTIAL AND PROPRIETARY AND  
REMAINS THE EXCLUSIVE PROPERTY OF AXIOMATIC TECHNOLOGIES CORPORATION. THIS  
DRAWING MAY NOT BE USED, REPRODUCED IN WHOLE OR IN PART, NOR REVEALED TO  
OTHERS WITHOUT THE PRIOR WRITTEN CONSENT OF AXIOMATIC TECHNOLOGIES  
CORPORATION. BY ACCEPTANCE OF THIS DRAWING, THE BEARER AGREES TO THESE  
CONDITIONS.

**AXIOMATIC**  
Global Electronic Solutions  
AXIOMATIC TECHNOLOGIES  
CORPORATION  
5915 WALLACE ST.  
MISSISSAUGA, ON  
CANADA L4Z1Z8  
905-602-9270