



Ø4.37 mm
[.172 in]
to suit an M4
or #8 bolt (2 places)

56.00 mm
[2.205 in]

30.58 mm
[1.204 in]

50.39 mm
[1.984 in]

(88.23 mm)
[3.474 in]

30.61 mm
[1.205 in]

33.28 mm
[1.310 in]

DETAIL A

molded in Deutsch IPD receptacle,
based on DT04-08PA, mates
with DT06-08SA

33.35 mm
[1.313 in]

70.00 mm
[2.756 in]

10.80 mm
[.425 in]



label detail

TOLERANCES			
fabrication		machining	
X.XXX	+/- 0.015	X.XXX	+/- 0.001
X.XX	+/- 0.031	X.XX	+/- 0.005
X.X	+/- 0.031	X.X	+/- 0.015
fractional	+/- 0.031	fractional	+/- 0.031

<small>PROPRIETARY</small> THE INFORMATION CONTAINED IN THIS DRAWING IS CONFIDENTIAL AND PROPRIETARY AND REMAINS THE EXCLUSIVE PROPERTY OF AXIOMATIC TECHNOLOGIES CORPORATION. THIS DRAWING MAY NOT BE USED, REPRODUCED IN WHOLE OR IN PART, NOR REVEALED TO OTHERS WITHOUT THE PRIOR WRITTEN CONSENT OF AXIOMATIC TECHNOLOGIES CORPORATION. BY ACCEPTANCE OF THIS DRAWING, THE BEARER AGREES TO THESE CONDITIONS.		AXIOMATIC TECHNOLOGIES CORPORATION 5915 WALLACE ST. MISSISSAUGA, ON CANADA L4Z1Z8 905-602-9270	
MATERIAL	DRAWN	DATE	TITLE
injection molded glass filled PA66 ultrasonically welded	TF	27/08/2015	1 Input 1 Output CAN Controller, J1939
	CHECKED	DATE	DWG REV
	DL		D1
	APPROVED	DATE	DWG NO
	DL		AX021610-MD
			PART NO
			AX021610
			SHEET
			1 of 1