


Universal Input, Single Output Valve Controller (5A)

With Near Field Communication (NFC)
Configurable with Android and Apple iOS Devices and Smartphones
P/N: AX020720-1.5M

Features:

- 1 universal signal input, user selectable as:
 - Voltage
 - Current
 - PWM
 - Frequency
 - Digital
- 1 output drives a solenoid, user selectable as:
 - Proportional current 0-5A
 - Proportional voltage up to Vps
 - Digital Hotshot
 - PWM signal
 - Digital on/off
- 1 auxiliary 0-5V output feedback
- +5V Reference output
- 12 or 24 VDC nominal
- PCB assembly with 4 2-pin push-in terminal blocks
- Multiple LED indicators
- IP67 for Metal Box once the cable is properly installed.
- Smartphone with E-Write NFC Android application configures the controller when placed in proximity. The application is also available for Apple iOS devices like iPhones.
- E-Write NFC provides flexible user configurability for application-specific input-output relationship with slope or time response.
- Protected and secure communication



Ordering Part Numbers:

AX020720-1.5M - Universal Input, Single Valve Controller, NFC, 1 8-pin Screw Terminal Block, Metal Box, 1.5 M Cable

AX020720 – Universal Input, Single Valve Controller, NFC, 1 8-pin Screw Terminal Block, PCB

AX020720-PG9 - Universal Input, Single Valve Controller, NFC, 1 8-pin Screw Terminal Block, Metal Box, Strain Relief (1 PG9)

If custom settings are requested, a unique part number will be assigned before ordering.

Description:

As a highly flexible controller, it accepts one command signal input and drives a solenoid up to 5 A. Many control profile parameters are user configurable. A PCB form factor is available. Operation is from -40 to 85°C. Designed to interface with 12 or 24 V battery power, it is suitable for machine and industrial applications.

Table 1.0 –User Configurable Universal Input																																									
Analog Input Functions	Voltage Input or Current Input																																								
Voltage Input	0-5 V (Impedance 110 kΩ) 0-10 V (Impedance 130 kΩ) +/- 5V (Impedance 110 kΩ) +/- 10V (Impedance 130 kΩ)																																								
Current Input	0-20 mA (Impedance 249 Ω) 4-20 mA (Impedance 249 Ω)																																								
Discrete Input Functions	Digital Input, PWM Input or Frequency Input																																								
Input	12-bit ADC																																								
Digital Input Level	Accepts 5V TTL and up to Vps Threshold: Low <1 V; High >2.2 V																																								
Digital Input	Active High or Active Low Amplitude: 0 to +Vps																																								
Input Impedance	1 MOhm High impedance, 10KOhm pull down, 10KOhm pull up to +6V																																								
PWM Input	Low Frequency (10 Hz to 1 kHz) High Frequency (100 Hz to 10 kHz) 0 to 100% D.C.																																								
Frequency Input	0.5 Hz to 50 Hz; 10 Hz to 1 kHz; or 100 Hz to 10 kHz 1 to 99% D.C.																																								
Input Accuracy	< 1%																																								
Input	16-bit Timer																																								
Maximum and Minimum Ratings	<table border="1"> <thead> <tr> <th>Characteristic</th> <th>Min</th> <th>Max</th> <th>Units</th> </tr> </thead> <tbody> <tr> <td>Power Supply</td> <td>9</td> <td>36</td> <td>V dc</td> </tr> <tr> <td>Voltage Input</td> <td>0</td> <td>36</td> <td>V dc</td> </tr> <tr> <td>Current Input 0(4)-20 mA</td> <td>0</td> <td>12</td> <td>Vdc</td> </tr> <tr> <td>Digital Input</td> <td>0</td> <td>36</td> <td>Vdc</td> </tr> <tr> <td>PWM Duty Cycle</td> <td>0</td> <td>100</td> <td>%</td> </tr> <tr> <td>PWM Low Frequency</td> <td>10</td> <td>1 000</td> <td>Hz</td> </tr> <tr> <td>PWM High Frequency</td> <td>100</td> <td>10 000</td> <td>Hz</td> </tr> <tr> <td>PWM Voltage pk - pk</td> <td>0</td> <td>36</td> <td>V dc</td> </tr> <tr> <td>Frequency</td> <td>0.5</td> <td>10 000</td> <td>Hz</td> </tr> </tbody> </table>	Characteristic	Min	Max	Units	Power Supply	9	36	V dc	Voltage Input	0	36	V dc	Current Input 0(4)-20 mA	0	12	Vdc	Digital Input	0	36	Vdc	PWM Duty Cycle	0	100	%	PWM Low Frequency	10	1 000	Hz	PWM High Frequency	100	10 000	Hz	PWM Voltage pk - pk	0	36	V dc	Frequency	0.5	10 000	Hz
Characteristic	Min	Max	Units																																						
Power Supply	9	36	V dc																																						
Voltage Input	0	36	V dc																																						
Current Input 0(4)-20 mA	0	12	Vdc																																						
Digital Input	0	36	Vdc																																						
PWM Duty Cycle	0	100	%																																						
PWM Low Frequency	10	1 000	Hz																																						
PWM High Frequency	100	10 000	Hz																																						
PWM Voltage pk - pk	0	36	V dc																																						
Frequency	0.5	10 000	Hz																																						

Lookup Table Specifications

Lookup Table	Can be used to create different input-to-output responses Ramp or Time Response Up to 5 Slopes/Time slots The user can map the Universal Input as control to the Lookup Table and configure the required slopes for the output
--------------	---

Output Specifications

Output	Up to 5A Half-bridge, High Side Sourcing, Current Sensing, Grounded Load High Frequency (25 kHz) The user can select the following options for output using the E-Write NFC. <ul style="list-style-type: none"> • Proportional Output Current (with current sensing) (0-5A) • Proportional Output Voltage (up to Vps) • Digital Hotshot • Output PWM Duty Cycle (0-100% D.C.) • Digital On/Off (Gnd-Vps) 																					
Configurable Parameters	Refer to Table 2.0.																					
	<table border="1"> <thead> <tr> <th colspan="3">Table 2.0 Configurable Output Parameters</th> </tr> <tr> <th>Parameter</th> <th>Minimum Range</th> <th>Maximum Range</th> </tr> </thead> <tbody> <tr> <td>Output Current</td> <td>0A</td> <td>5A</td> </tr> <tr> <td>Ramp Up / Ramp Down</td> <td>0ms (no ramp)</td> <td>60,000ms</td> </tr> <tr> <td>Dither amplitude (level)</td> <td>0mA (no dither)</td> <td>400mA</td> </tr> <tr> <td>Current dither frequency</td> <td>50Hz</td> <td>500Hz</td> </tr> <tr> <td>PWM frequency</td> <td>1Hz</td> <td>25kHz</td> </tr> </tbody> </table>	Table 2.0 Configurable Output Parameters			Parameter	Minimum Range	Maximum Range	Output Current	0A	5A	Ramp Up / Ramp Down	0ms (no ramp)	60,000ms	Dither amplitude (level)	0mA (no dither)	400mA	Current dither frequency	50Hz	500Hz	PWM frequency	1Hz	25kHz
Table 2.0 Configurable Output Parameters																						
Parameter	Minimum Range	Maximum Range																				
Output Current	0A	5A																				
Ramp Up / Ramp Down	0ms (no ramp)	60,000ms																				
Dither amplitude (level)	0mA (no dither)	400mA																				
Current dither frequency	50Hz	500Hz																				
PWM frequency	1Hz	25kHz																				
Output Accuracy	Output Current mode ≤1% Output Voltage mode ≤1% Output PWM Duty Cycle mode ≤1%																					

Output Resolution	Output Current mode 1 mA Output Voltage mode 0.1V Output PWM mode 0.1%
Protection	Overcurrent and short circuit protection
Auxiliary Output	0-5V output is proportional to the proportional output range. Short circuit protection is provided.
Auxiliary Output Scale	20% of proportional output range
Voltage Reference	+5V, 50 mA maximum load

General Specifications

Microcontroller	STM32F205RET6 32-bit, 512 Kbit program flash																		
Quiescent Current	34 mA @ 24Vdc																		
LED Indicator	Power, heartbeat, input fault indication and output fault indication																		
Control Logic	User configurable																		
Communications	Near Field Communication Full-duplex Data rate: 106 kbit/s Complies with ISO1443 (RF protocol), ISO13239, and ISO7816 Protected and secure configuration																		
User Interface	E-WRITE NFC Application is available from Google Play for Android devices. https://play.google.com/store/apps/details?id=axiomatic.nfcproject The application is also available for Apple iOS devices like iPhones.																		
Operating Conditions	-40 to 85 °C (-40 to 185 °F)																		
Dimensions – In Metal Box with strain relief	Metal Box with gasket and PG9 strain relief 114.3 x 27.9 x 79.4 mm 4.50 x 1.01 x 3.13 inches (W x D x H excluding PG9 strain relief) The cable is 1.5M in length and its terminals are unterminated. Refer to Figure 1.0.																		
Protection	IP00 for PCB IP67 for Metal Box once cable is added																		
Vibration	Preliminary values: MIL-STD-202G, Method 204D test condition C (Sine) and Method 214A, test condition B (Random) 10 g peak (Sine) 7.68 Grms peak (Random)																		
Shock	Preliminary values: MIL-STD-202G, Method 213B, test condition A 50g (half sine pulse, 9ms long, 8 per axis)																		
Approvals	CE / UKCA marking																		
Weight	1.0 lb. (0.453 kg)																		
Electrical Connections	1 8-pin screw terminal block (Wieland P/N: 25.197.0853.0) Use 18-20 AWG wire for connection to power and solenoid. <table border="1" data-bbox="591 1335 1040 1602"> <thead> <tr> <th>PIN #</th> <th>FUNCTION</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>POWER -</td> </tr> <tr> <td>2</td> <td>POWER +</td> </tr> <tr> <td>3</td> <td>SOLENOID -</td> </tr> <tr> <td>4</td> <td>SOLENOID +</td> </tr> <tr> <td>5</td> <td>INPUT +</td> </tr> <tr> <td>6</td> <td>INPUT GND</td> </tr> <tr> <td>7</td> <td>AUXILIARY OUTPUT</td> </tr> <tr> <td>8</td> <td>+5V REFERENCE</td> </tr> </tbody> </table>	PIN #	FUNCTION	1	POWER -	2	POWER +	3	SOLENOID -	4	SOLENOID +	5	INPUT +	6	INPUT GND	7	AUXILIARY OUTPUT	8	+5V REFERENCE
PIN #	FUNCTION																		
1	POWER -																		
2	POWER +																		
3	SOLENOID -																		
4	SOLENOID +																		
5	INPUT +																		
6	INPUT GND																		
7	AUXILIARY OUTPUT																		
8	+5V REFERENCE																		
Mounting	<u>Note:</u> Program the PCB assembly before installing it in the metal box. Mounting holes are sized for #10 or M6 bolts. The bolt length will be determined by the end-user's mounting plate thickness. The mounting flange of the controller is 0.062 inches (1.6 mm) thick. If the module is mounted without an enclosure, it should be mounted vertically with connectors facing left or right to reduce the likelihood of moisture entry. All field wiring should be suitable for the operating temperature range. Install the unit with appropriate space available for servicing and for adequate wire harness access.																		

Dimensional Drawing




Figure 1.0 – Dimensional Drawing

Form: TDAX020720-1.5M-03/14/2024